



12Gb/s SAS Enterprise 2.5" SSDs

## Lightning Eco™ Gen. II SAS SSDs

Maximize bandwidth with low latency read speeds for the highest, most cost-effective performance

### Features

- Full data path protection, End-to-end T10-DIF support
- Temperature-based performance control
- MTBF - 2.5 Million Hours<sup>3</sup>
- 5 Year Warranty<sup>4</sup>

### Benefits

- High, Predictable Performance
- Industry-leading Reliability
- Highest Cost-to-performance value
- Low latency data access for high quality of service (QoS)
- Maximum bandwidth for high speed data transfer rates

### Read-Intensive Application Workloads

- Data Warehousing
- Web Servers
- Media Streaming
- Virtual Tape Libraries (VTL)
- Video on Demand (VOD)
- Web-Based Applications
- File Servers

The Lightning Eco™ Gen. II 12Gb/s SAS SSD from SanDisk® doubles interface speed, providing the highest performance for mission-critical hyperscale, cloud and virtualized data center application workloads. This next generation Lightning® SSD offers a feature-rich robust design, combined with SanDisk's custom controller and innovative parallel processing architecture to deliver full data path protection (T10-DIF support), temperature based power control, SED instant secure erase, an MTBF of 2.5 million hours, and power fail protection. This SSD is backward-compatible with 6Gb/s SAS and offers a single firmware binary platform for seamless integration and reduced qualification times.

Lightning Eco™ Gen. II SAS SSDs offer solid I/O cost to performance benefits with low latency data access for high quality of service (QoS). Available in 19nm eMLC capacities from 800GB - 1.6TB<sup>2</sup> and with random read/write performance of up to 195K/80K IOPS\* and sequential read/write speed of up to 980/600 MB/s<sup>1</sup>/\*. These SSDs are designed for read-intensive applications such as Data Warehousing, Media Streaming, Video on Demand (VOD), Web-based Applications, Virtual Tape Libraries (VTL) and File Servers, with a heavy read workload comprised of a 90/10 read/write mix. This SSD offers 3 full drive writes per day (DWPD) with a limited 5 year warranty<sup>4</sup>.

Lightning Eco Gen. II SAS SSDs are a product of SanDisk's vertical integration - spanning from the fabrication of the NAND technology and wafer to the manufacturing of the finished SSD. This vertical integration, results in a customized solution that takes full advantage of each component to deliver maximum performance and quality assurance. Lightning Eco Gen. II SSDs provide high, predictable performance, industry-leading reliability and maximum value.

## Lightning Eco™ Gen. II 12Gb/s SAS 2.5" SSDs

800GB - 1.6TB

Performance/IOPS	
Data Throughput (Sequential Read/Write) <sup>1</sup> /*	Up to 980/600 MB/s
Total IOPS* (Random Read) 4KB - (single port)	Up to 195,000 IOPS
Total IOPS* (Random Write) 4KB - (single port)	Up to 80,000 IOPS
Interface, Capacity, and Memory Technology	
Host Interface	12Gb/s SAS
Interface Ports	Dual full-duplex
Form Factor	2.5 inch
19nm eMLC User Capacities <sup>2</sup>	800GB, 1.6TB
Sector Sizes Supported	512, 520, 4K bytes/sector T10-DIF 1, DIF 2 Support
Reliability	
MLC Page Pairing Protection	No risk of data loss
Unrecovered Bit Error Rate (UBER)	<1 sector in 10 <sup>18</sup> bits read**
End-to-End Data Protection	No performance impact
Patrol Read (automatic)	No performance impact
Power-on Hours	8760 hours per year
MTBF <sup>3</sup>	2.5 million hours
Warranty <sup>4</sup>	Lesser of 5 years or maximum endurance used
Endurance	
DWPD (Random Read)	3 DWPD
Physical Dimensions	
Height (max)	15.0 mm
Width (max)	70.1 mm
Length (max)	100.45 mm
Weight	0.238 Kg
Power Consumption	
Idle	3.9 watts
Typical	5.9 watts
Environment	
Operating Temperature (ambient)	0 to 60° C
Non-operating Temperature	-40 to 85° C
Start-up Time (Power-on to Ready)	<15 seconds

## Lightning Eco™ Gen. II 12Gb/s SAS 2.5" SSDs - Ordering Information

Part Number	Capacity
SDLTODKR-800G-5Cxx	800GB
SDLTOCKR-016T-5Cxx	1.6TB

### xx - Pack Out Option:

Generic/Sample:	A1
10 Pack:	02
Bulk Pack:	03

Specifications subject to change without notice. All specifications are based on an 11W performance level.

\*Performance may vary by capacity.

\*\*1 recoverable error in 10<sup>18</sup>.

(1) Based on direct attached SAS performance testing, performance may be lower depending upon host device, OS and application.

(2) 1 gigabyte (GB) = 1 billion bytes. Some capacity not available for data storage.

(3) MTBF - Mean Time Between Failures based on parts stress analysis.

(4) The earlier of (I) five (5) years or (II) the time at which such Product unit's total cumulative data recorded on such unit at its S.M.A.R.T. attribute (log page 2Fh, parameter 25) or log page 11h, parameter 1 (Percentage Used Endurance Indicator) reaches 100% of the Product unit's endurance value. For more warranty information, please visit kb.sandisk.com.

© 2016 Western Digital Corporation. All rights reserved. SanDisk and the SanDisk logo are trademarks of Western Digital Corporation or its affiliates, registered in the United States and other countries. Lightning Eco is a trademark of Western Digital Corporation or its affiliates. Other brand names mentioned herein are for identification purposes only and may be the trademarks of their holder(s). Lightning ECO Datasheet 061516.

### Contact information

datacentersales@sandisk.com

### Western Digital Technologies, Inc.

951 SanDisk Drive  
Milpitas, CA 95035-7933, USA  
T: 1-866-744-2165

Western Digital Technologies, Inc. is the seller of record and licensee in the Americas of SanDisk® products.

For more information, please visit:

[www.sandisk.com/enterprise](http://www.sandisk.com/enterprise)

# SanDisk®

a Western Digital brand

At SanDisk, we're expanding the possibilities of data storage. For more than 25 years, SanDisk's ideas have helped transform the industry, delivering next generation storage solutions for consumers and businesses around the globe.